

MATERIAL

Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP

Insulation Resistance : 5000MΩMin. at DC 500V




Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

Operation Temperature : -40°C to + 105°C

TOLERANCES ARE

- X.±
- .X±
- .XX±
- .XXX±
- ANG±



Recommended P.C.B Layout

RoHS Compliant

☆ Special Type

POLES	DIM A	DIM B	DIM C
☆6	12.66	10.26	5.08
6	15.20	12.80	5.08
☆8	15.20	12.80	7.62
8	17.78	15.48	7.62
10	20.30	18.10	10.16
12	22.84	20.64	12.70
14	25.38	23.18	15.24
16	27.92	25.72	17.78
20	33.00	30.80	22.86
24	38.08	35.88	27.94
26	40.62	38.42	30.48
30	45.70	43.50	35.56
34	50.80	48.58	40.64
40	58.40	56.20	48.26
44	63.48	61.28	53.34
50	71.10	68.90	60.96
56	78.72	76.52	68.58
60	83.80	81.60	73.66
64	88.88	86.68	78.74

DESCRIPTION: BOX HEADER 2.54*2.54mm, STRAIGHT T,PE,